



MS852+ ESD

High Performance 2D Imager ESD Scanner

The MS852+ ESD (Electrostatic discharge) imager is a high-performance device but additional designed to satisfy the stringent requirements of cleanrooms and static-safe manufacturing environments.

ESD Protection

unitech's MS852+ ESD-safe scanner is made by internal mixed way with antistatic agent to protect MS852+ series to be ESD safe to be used at ESD protected area including its cable. With the Internal mixed way, the body of the product and its cable can withstand ESD up to $10^5 \sim 10^9$ ohms per square and no containing Chlorine material. The Internal mixed way can provide a longer time of ESD protection than external addition way due to external additional anti-static in the latter part of the packaging or processing process was wiped away. An internal mixed antistatic agent can continue to add antistatic agent to the plastic surface, to make up the surface due to wipe and the amount of antistatic agent consumed. It is a reliable tool to streamline your workflow in manufacturing environments.

Increase Productivity with Superior Industrial Barcode Scanner

Specially built for challenging work environment, the MS852+ ESD is built in Megapixel barcode sensor that enhances the maximum compatibility to capture most 1D / 2D barcodes on mobile screens, even damaged or poorly printed barcodes and special barcode symbologies such as OCR on passport, Dot codes on tires or cigarette package, and Digimarc barcode on special retail packages. With its advanced barcode technology and durable design, the MS852+ ESD handheld scanner is a highly reliable tool to increase productivity and efficiency.

Ultra-Durability

With excellent motion tolerance design, the MS852+ ESD increased scan speed and operational effectiveness even while moving. Equipped with a louder beeper and brighter LED indicators, the MS852+ ESD allows users to recognize the feedbacks easily even in dark environment. While sustaining a 2.1 meter drop to concrete, MS852+ ESD incorporated with IP42 rugged design for protection against dust and moisture. Moreover, the built-in long lifecycle trigger of 10 million times guarantees a continuous productivity for best reliability. This scanner can be used in the most practical way depending on the scanning task in various solutions in retail, logistics, manufacturing, hospitality, and government.

Features

- Withstands ESD up to $10^5 \sim 10^9$ ohms per square
- Megapixel barcode sensor that enhances the maximum compatibility
- Support most 1D / 2D barcode on mobile screens, even damaged or poorly printed barcodes
- Support OCR, Dot codes, and Digimarc barcodes
- With excellent motion tolerance design suitable to read bar code while moving
- Long lifecycle trigger design: Up to 10,000,000 times.
- Ultra-rugged design : IP42 and 2.1m drop spec
- Louder beeper and brighter LED indicators for easily recognizing feedbacks



MS852+ ESD

Specifications

Optical & Performance

Sensor	1280 X 800 global shutter
Aiming Element	Red laser or 528 nm visible green LED
Illumination	White or Red LED
Imager Field of View	100,000 Lux (Sunlight)
Skew Angle	±60°
Pitch Angle Sensor	±60°
Roll Angle	360°
Optical Resolution	1D 3mil/ 0.075mm
Printing Contrast Scale	20% minimum print contrast ratio
Depth of Field (DOF PCS=80%)	SYMBOLGY / X-DIM TYPICAL RANGE* Near Far
	13 mil UPC 1.34 in / 3.4 cm 22.5 in / 57.3 cm
	5 mil Code 39 2.76 in / 7 cm 11.85 in / 30.1 cm
	10 mil Code 39 1.14 in / 2.9 cm 20.3 in / 51.7 cm
	20 mil Code 39 1.38 in / 3.5 cm 31.5 in / 80 cm
	15 mil Code 128 1.34 in / 3.4 cm 25.6 in / 65 cm
	10 mil DM 2.84 in / 7.2 cm 11.7 in / 29.7 cm
	6,7 mil PDF417 3.3 in / 8.4 cm 9.6 in / 24.4 cm
	15 mil QR Code 1.3 in / 3.3 cm 15.35 in / 39 cm

Communication

Host Interface supported	USB
--------------------------	-----

Mechanical

Dimension	87.8 L x 71.6 W x 177.7 H (mm)
Weight	165g
Trigger Switch Life	10 million times

Regulatory Approvals

CE, FCC, BSMI, VCCI

Accessories

Standard Hands Free Stand (Optional)

Symbologies

1D	Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data Bar, TLC39
2D	2D Stacked: Codablock A, Codablock F, PDF417, MicroPDF417 2D Matrix: Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin), Grid Matrix, Dot Code Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet
Postal Codes	

Electrical

Power Requirement	4 VDC to 5.5 VDC
Current	Operating: 252mA Standby: 77mA

Environmental

ESD Protection	Functional after 8K Contact and 15K Air
Mechanical Shock	2.1M onto concrete (scanner only)
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Relative Humidity	95% non-condensing
IP Rating	IP42

Package Contents

Scanner + Cable



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com

Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

